



EXCAVATOR

R57 PRO



MEET THE NEW GENERATION OF RIPPA MACHINES

Lift your business to the next level with the R57 PRO
RIPPA excavators. Exceptionally powerful, yet environmentally friendly,
The R57 PRO excavators feature extraordinary fuel efficiency



RAISE PROFITS, PRODUCTIVITY & FUEL EFFICIENCY

TOP PERFORMANCE IN A VERSATILE PACKAGE

A compact & powerful machine for the best adaptability to any work site. Large hydraulic capacity of a tool carrier. Works in narrow spaces thanks an ultra-compact design and boom swing.

EFFICIENCY

The new R57 PRO offer really high level of efficiency, in any application, thanks to a brand new design. The R57 PRO offers the best compactness in the market, where the R57 PRO offers the best compromise between compactness and lifting performance, when heavy lifting is needed.

MANEUVERABILITY

The smooth and precise hydraulic system can drive all the attachments needed on the construction site. The operator can control the flow proportionally. Pedal driving can be operated by manual lever without using pedals. The two travel modes can be switched at any time.



EASY MAINTENANCE

Easy access from ground level to all components, filters and refilling points.

The R57 PRO was designed to be easy to keep on the job. Offers easy access to filters, fluids and all service points — including the engine, pump package, valve bank, cooling system and plumbing.

Quick and easy machine diagnosis allows you to monitor critical systems in real time from the LCD monitor in the cab.

PRODUCTIVITY

Superior digging, pulling and traction forces to face all jobsites.

SAFETY

Anti-collision net (optional)

Powerful LED lighting with large glass door for excellent visibility

Pilot safety lock

ROPS cab

OPG protective cover (optional)

COMFORT

low noise & vibration levels and excellent all-round visibility.

Large glass door for easy access and better visibility.

Fully adjustable heated air suspension seat, air conditioning with climate control as standard.

ALL-ROUND VERSATILITY AND IMPROVED FUEL EFFICIENCY



A MODEL WITH NOVEL FEATURES

control for the hydraulic system and for the engine

- Improved ergonomics, increased comfort and excellent all-round visibility, Improved reliability, using high-performance materials - combined with new methods of structural stress analysis - have increased component life expectancy, thus reducing running costs
- Reduced maintenance increases the excavator's availability and lowers the operating costs

HIGHEST PERFORMANCE IN ANY WORK ENVIRONMENT

The advanced hydraulic system, combined with a powerful engine, provides the biggest digging and tractive forces for efficient operation. As a result, the R57PRO provides outstanding performance, work efficiency and the ability to adapt to any work environment.

Kubota V2607 (EPA4/Euro 5)

The R57 PRO has a powerful and eco-friendly heart, always providing high operating efficiency and pleasant working conditions.

BOOM SWING

The boom swing function allows you to work in very narrow areas

POWERFUL DIGGING FORCE (BUCKET)

Powerful, efficient, and with increased digging force can face every job site condition.

DOZER BLADE

Welded, unitized blade provides durability even under harsh working conditions.

DUAL-SPEED FAST AND SLOW

The fast gear is suitable for fast movement of equipment within the site, saving transition time, improving overall construction efficiency, precise control, and adapting to various working conditions



THE IDEAL WORKSPACE DESIGNED AROUND YOU

- 1 Seat
- 2 Arm rest
- 3 Left-hand work lever(joystick)
- 4 Assistive device buttons
- 5 travel pedal
- 6 Foot vent
- 7 Defrodter vent
- 8 Travel lever
- 9 Display monitor
- 10 Right-hand work lever (joystick)
- 11 Dozer lever
- 12 Cup holder
- 13 Safety lever
- 14 Starter switch
- 15 Cigarette lighter
- 16 Radio
- 17 Air conditioning panel



The cabin has been ergonomically designed with comfort in mind

The R57PRO are designed to provide you with the best possible working conditions. Its spacious interior offers a fully adjustable and comfortable seat. Comfortably seated, you have easy access to several storage compartments and a clear all-round view of the worksite. Noise and vibration levels are reduced while air conditioning allows you to maximise your productivity and return on investment.



MORE DURABILITY –LESS MAINTENANCE

A reinforced chassis provides strength, while the optimised boom shape ensures uniform load distribution for more durability. Top quality materials, the most advanced computer-aided design and endurance testing under the most demanding conditions ensure your excavator will keep on performing. The R57PRO are designed for low maintenance with longer intervals resulting in more machine availability on site while skilled RIPPA-trained technicians are available to provide extra support when needed.



MORE DURABILITY — LESS MAINTENANCE

The most advanced technology developed by RIPPA. Was integrated into the R57PRO excavators for powerful performance and simple, easy maintenance. This provides the operator with convenient maintenance check points and maximizes the R57PRO's work efficiency.



BEST MAINTENANCE ACCESS

MAINTENANCE ACCESS MADE SIMPLE

A battery cut-of switch makes it easy to disconnect the battery during long-term storage

The hour meter display can be easily checked from ground level - For extra accessibility and servicing convenience, all filters

AIR BREATHER

It can effectively block dust, sand and other impurities in the air, prevent them from entering the engine cylinder, avoid wear and failure, and extend the life of the engine.

ENGINE ROOM

The engine compartment is designed for easier service, and the sturdy sound-proofing inside the engine cover reduces the noise to provide a more comfortable environment for the operator and those working around the machine.

TRACKS

The standard steel crawler has a solid structure and is suitable for heavy-duty conditions. It can support a larger machine weight and operating load, and has strong stability. The optional rubber crawler has stronger anti-skid and grip, and causes less damage to sidewalks and roads in urban environments.

OIL GAUGE

Hydraulic oil level can be easily checked through the gauge on the side of the hydraulic tank.

GREASE PIPING

Integrated grease piping is designed for easy maintenance of the swing bearing and boom swing cylinder.

EXTERNAL FUEL CAP

The external lockable fuel tank cap makes refueling easier and safer. When the oil level reaches the minimum, a warning beep sounds for added convenience.

ENGINE HOOD HYDRAULIC SUPPORT

No need for manual support, one-button opening saves effort and time, and improves maintenance efficiency. The hydraulic rod can firmly support the engine cover to avoid accidental falling, ensure the safety of maintenance personnel, and the support angle is reasonable, with larger inspection space, making daily maintenance and repair work smoother.



ASSISTIVE DEVICES



Breaker



Scarifier



Compactor



Pile hammer



Crushing pliers



Double cylinder hydraulic shears



Single cylinder crushing shear



Rotating log grapple



Screen bucket



Strengthen rock bucket




Rake



Hawkbill scissors

ENVELOPE DIAGRAM



CONFIGURATION

Optional/ Additional	Cab	Standard
	AC	Standard
	Reversing camera	Optional
	Control handle	Pilot hydraulic
	Boom swing	None
	Bulldozer swing	Optional
	Change color	Optional
	Steel track, rubber track	Optional
	Hydraulic thumb clamp	Optional
	Attachments	Quick change
Breaker		Optional
Ripper		Optional
Rake		Optional
Hydraulic wood grabber		Optional
Mower		Optional

PARAMETER

	unit	SI	US
Basic Information	Machine working weight	kg / lb	5775kg / 12705lb
	Bucket capacity	m ³ / ft ³	0.175m ³ / 6.18ft ³
	Travel speed low/high speed	km/h / mph	0-2.4/0-3.8km/h / 0-1.5/0-2.4mph
	Gradeability	%	35% / 35%
	Ground pressure	kpa / psi	35.4kpa / 5.1psi
Machine parameters	Maximum digging force	KN / lbf	32KN / 7194lbf
	Maximum digging radius	mm / in	6160mm / 242.5in
	Maximum digging depth	mm / in	3785mm / 149in
	Maximum digging height	mm / in	5810mm / 228.7in
	Maximum unloading height	mm / in	4080mm / 160.6in
	Maximum deflection angle	mm / in	- / -
	Track extension range	mm / in	- / -
	Engine brand		Kubota / Kubota
	Engine model		V2607 / V2607
	Maximum horsepower	ps/hp	48.3ps / 47.6hp
	Maximum power	kw	35.5kw / 35.5kw
	Maximum speed	rpm	2200rpm / 2200rpm
	Displacement	L / gal	2.615L / 0.69gal
	Number of cylinders		4 / 4
	Cooling method		Water-cooled / Water-cooled
	Engine oil change amount	L / gal	6.1L / 1.6gal
	Fuel form		Diesel / Diesel
	Fuel grade		0/-10 / 0/-10
	Theoretical fuel consumption		9.72L/h / 9.72L/h
	Transport length	mm / in	5850mm / 230.3in
	Transport width	mm / in	2000mm / 78.7in
	Transport height	mm / in	2580mm / 101.6in
	Counterweight ground clearance	mm / in	669mm / 26.3in
	Bucket width	mm / in	600mm / 23.6in
	Boom length	mm / in	3000mm / 118.16in
	Arm length	mm / in	1600mm / 63in
	Bulldozer blade width	mm / in	1880mm / 74in
Main pump type/model		Load sensitive variable piston pump/68	
Main pump brand		HYTEK / HYTEK	
Main pump maximum flow	L/min / gpm	149.6L/min / 39.5GPM	
Transport parameters	Multi-way valve		8-way hydraulic multi-way valve
	Multi-way valve brand		HYTEK / HYTEK
	Rated set pressure	mpa/ psi	22.5MPa / 3263psi
	Maximum set pressure	mpa/ psi	25MPa / 3626psi
	Travel hydraulic motor type		TM07 / TM07
	Travel motor brand		ZHTE / ZHTE
	Motor displacement	ml/r	22-44ml/r / 22-44ml/r
	Slewing hydraulic motor type		ZHTE DH80 / ZHTE DH80
Displacement	ml/r	43.2ml/r / 43.2ml/r	